FEATURES OF POWERKING HYDRAULIC BREAKERS

Our abundant experiences make it possible :

- Great Power
- Excellent durability
- Low noise and vibration
- Precise operation
- Fantastic efficiency at hard and sticky rock
- HARDOX in the bracket(Option)



• Specification

Model	Operating Weight		Overall Height		Operating Pressure		Required Oil Flow		Number of Blow	Impact Energy		Rod Dia.		Suitable Excavator	
	kg	lbs	mm	inch	kg/cm²	psi	Lpm	Gpm	bpm	Joule	ft-lbs	mm	inch	ton	lbs
PK10T	99	218	1,115	43.9	80-110	1,136-1,562	15-25	3.9-6.6	800-1,230	210	155	40	1.6	0.5-1.5	1,100-3,300
PK20T	152	334	1,251	49.3	80-110	1,136-1,562	20-30	5.3-7.9	600-1,000	260	192	45	1.8	0.8-3	1,760-6,600
PK30T	179	394	1,372	54.0	90-120	1,278-1,704	25-40	6.6-10.5	550-950	368	271	53	2.1	1.2-4	2,600-8,800
PK45T	292	642	1,641	64.6	95-130	1,349-1,846	30-45	7.9-11.9	450-750	730	538	68	2.7	4-7	8,800-15,400
PK60T	430	946	1,804	71.0	95-130	1,349-1,846	40-80	10.5-21.0	400-800	1040	766	80	3.1	5-9	11,000-19,800
PK70T	576	1,267	2,099	82.6	130-150	1,846-2,130	45-85	11.9-22.5	400-800	1,316	970	85	3.3	8-11	17,600-24,200
PK100T	850	1,870	2,339	92.1	150-170	2,130-2,414	80-110	21.1-29.1	450-630	1,991	1,467	100	3.9	11-16	24,200-35,200
PK150T	1,312	2,886	2,545	100.2	150-170	2,130-2,414	90-120	23.8-31.7	400-900	2,400	1,769	120	4.7	12-20	26,400-44,000
PK220T	1,765	3,883	2,719	107.0	160-180	2,272-2,556	125-150	33.1-39.6	400-800	3,654	2,693	135	5.3	18-25	39,600-55,000
PK250T	1780	3,916	2,830	111.4	160-180	2,272-2,556	120-180	31.7-47.5	350-500	4,200	3,100	140	5.5	18-26	39,600-57,300
PK350T	2,300	5,060	2,951	116.2	160-190	2,272-2,698	160-180	42.3-47.5	300-650	5,180	3,818	150	5.9	28-35	61,600-77,000
PK450T	3,010	6,622	3,240	127.6	160-190	2,272-2,698	160-240	42.3-63.3	300-600	9,881	7,282	160	6.3	35-45	77,000-99,000
PK550T	4,200	9,240	3,800	149.6	160-190	2,272-2,698	250-320	66.1-84.6	250-500	12,020	8,859	180	7.1	45-70	99,000-154,000

The above specifications are subject to change without prior notice for the quality improvement