# CAK-H2000AT




## FEATURES

- Max. 2M(1920 x 1080) @30fps
- Min. illumination 0.1Lux @ F1.2, 30IRE (Color)
  0.01Lux @ F1.2, 30IRE (B/W)
- Built-in 3.5~16mm Auto-Focus lens
- Day&Night (Auto ICR)
- WDR / 3DNR
- OSD
- DC12V

## SPECIFICATION

| MODEL | CAK-H2000AT |
|---|---|
| **CAMERA** | |
| Image Sensor | 1/2.8" 2M Progressive Scan CMOS sensor (SONY) |
| Total Pixels | 2000(H) x 1241(V) |
| Scanning System | Progressive Scan |
| Shutter Speed | 1/25~1/120sec |
| S/N Ratio | More than 50dB |
| Lens | 3.5~16mm Auto-Focus Lens |
| Min. Illumination | COLOR : 0.1Lux @ F1.2, 30IRE<br>B/W : 0.01Lux @ F1.2, 30IRE |
| Day & Night | Auto / Day / Night (ICR) |
| AGC | Normal, High |
| White Balance | AUTO / PRESET / MANUAL |
| WDR / BLC | OFF / WDR / BLC |
| DNR | OFF / MID / HIGH |
| DSS | OFF, x2, x3, x4 |
| Image setting | Brightness, Sharpness |
| Other Functions | Image Flip, Mirror/ACE, Privacy masking |
| **GENERAL** | |
| Sensor In/Out | Built-in 1 Output |
| Video Out | HD-SDI, SMPTE-292M<br>(1280X720p/59.94Hz, 1280X720p/50Hz<br>1920X1080p/59.94Hz, 1920X1080p/50Hz) |
| Power | DC 12V, 5W |
| Approvals | FCC, CE, ROHS |
| Operating Temp. | -10°C ~ 50°C |
| Weight | 300 g |
| Dimension | Ø120 x 100.8(H) mm |

## DIMENSION

Unit : mm

