Series V70

RECTANGULAR GATE VALVE

PRESYS
PREMIUM SYSTEM

DOUBLE HOUSING TYPE



Application

_Plasma Etch, CVD, Sputter Deposition
_Manufacturing of solar panels
_Semiconductor processing
_LCD/frat panel precess
_All other cluster vacuum systems

Features

_Removable valve housing cover
_Semi standard application(Semi E21–94, Semi E24–92, Semi–E21.1–1296)
_Patented L–motion link and dual shifts without springs in the actuator enable faster, smoother actuation with signifi–cantly reduced vibration
_Dust seal on the vacuum side of the bonnet flange that virtually eliminates particulate from entering the bellows
_Mechanical locking so at the end of gate travel the valve locks into position
_Welded bellows actuator seal
_Bonnet flange bolts are designed with retainers to eliminate bolts from falling out upon disassembly
_Double rectangular housing to allow product to enter one side and exit the other

Options

_Custom sizes available
_Various o–ring compounds (Kalrez®, Chemraz®, etc.)

www.presys.kr

PREMIUM SYSTEM PRESYS

Head Office_ 2–1, Seoku–Dong, Hwaseong–Si, Gyeonggi–Do, Korea **Tel**_ +82–31–8003–1133 **Fax**_ +82–31–8003–3399
For further information, visit **www.presys.kr**, contact us at jw.jee@presys.kr