CAF-H2000PTZ



SPECIFICATION

- Max. 2M(1920 x 1080) @30fps
- 12x(5~60mm) optical zoom, 10x digital zoom
- WDR / Day&Night (Auto ICR)
- 210 Preset, 8 Pattern, 8 Scan, 8 Tour
- 4 Sensor Inputs & 1 Relay Output
- 360° Endless Pan, Tilt/ Zoom
- AC24V

MODEL	CAF-H2000PTZ
CAMERA	
Image Sensor	1/2.8" 2.0M Progressive Scan CMOS sensor
Total Pixels	2000(H) X 1241(V)
Effective Pixels	Approx. 2 Mega pixels
Aspect Ratio	HD: 16:9
Zoom	X5 Optical Zoom / X12 Digital Zoom
Focal Length	f = 5 ~ 25.0 mm, F3.5 ~ F3.7
Min. Illumination	COLOR : 0.5Lux @ F3.5, 30IRE B/W : 0.01Lux @ F3.5, 30IRE
Day&Night	Auto / Day / Night (ICR)
Focus	Auto / Manual
Shutter Speed	1/30(25)sec ~ 1/60000sec
DNR	OFF / LOW / MIDDLE / HIGH
AGC	Auto / MANUAL / MAX Gain Limit(21 steps)
White Balance	Auto / preset / Manual
WDR	OFF / WDR / BLC
PAN/TILT	
Range	Pan : 350°
	Tilt : 90°
Pan/Tilt Speed	Preset : 120°/ sec Manual : MAX 120°/sec
Preset	128 Presets with Labels
Pattern	4 Patterns
Scan	8 Scans
Group	8 Groups (MAX. 10 Entries for Each Group)
Schedule	7 Rules (Condition : Day, Time--> Action : Home, Preset, Scan, Group, Pattern)
GENERAL	
Sensor In/Out	Built-in 1 Input / 1 Output
Video Out	HD-SDI 1080/30p, 1080/25p 720/60p, 720/50p
Communication	RS-485
RS-485 Protocol	Auto(Pelco-D, Pelco-P, Samsung, Panasonic, Kalatel, Techwin can be supported automatically)
Power	DC 12V
Approvals	FCC, CE, IP66, ROHS
Outdoor Housing	Weather proof/Vandal Proof Structure Color: White Pearl
Operating Temp.	-10°C ~ 50°C
Weight	800 g
Dimension	Ø125 x 83(H) mm

DIMENSION

Unit : mm

