MPC-100A

PC Interface Unit

MDTC

Equipment Overview & Function

Description

○ This is a one input, 2 output R.G.B.H.V distribution amplifiers.

Features

○ It is split two outputs, one R.G.B.H.V signal to monitor, the other to R.G.B.H.V display devices such as projector, RGB SW etc.

○ And receives one audio signal such as computer and distributes to speakers and other audio equipment.

○ ON / OFF Switch is available in front of the device. D-sub Connector,3.5mm Stereo Mini Jack at input/output terminal makes operation easy.

Panel Drawing



Specifications

○ Video Part

- Input/Output number : 1 x 2
- Input/Output type : RGBHV
- Input/Output connector : d-sub 15pin
- Input/Output level : analog RGB : 1.2Vp-p Max, H-Sync, V-Sync : TTL level
- Input/Output impedance : 75Ohm ± 1%
- Bandwidth : 600 MHz (-3 dB), fully loaded

MAX **Max Digital Tech Co.,Ltd**

Copyright 2006 Max Digital Tech.All rights reserved

Lead the 21st century with technology and service ..

Asia	+65 81335582	Fax. +65 67828910
China	+86 021 54249750	Fax. +86 021 54240199
Singapore	+65 81335582	Fax. +65 67828910
Korea	+82 2 2026 1200	Fax. +82 2 2026 1217

MPC-100A

PC Interface Unit

Specifications

○ Audio Park

- Input/Output Port : 1 Input 2 Output
- Input/Output Connector : 3.5mm Stereo Mini Jack
- Frequency Response : ±0.1dB (20Hz ~ 20kHz)
- Input Impedance : 10K Ohm
- Output Impedance : 50 Ohm

○ Case & Power Part

- Power source : DC 9V 1A (Power Adaptor)
- Temperature : 0℃ ~ 40℃
- Type : desk type
- Dimensions : 150(W) * 30(H) * 104(D) mm

Max Digital Tech Co.,Ltd

Copyright 2006 Max Digital Tech.All rights reserved

Lead the 21st century with technology and service ..

Asia	+65 81335582	Fax. +65 67828910
China	+86 021 54249750	Fax. +86 021 54240199
Singapore	+65 81335582	Fax. +65 67828910
Korea	+82 2 2026 1200	Fax. +82 2 2026 1217