MDVI-30A

DVI REPEATER

장비개요 및 성능

Description

○ 본 장비는 장거리 전송 되어진 하나의 싱글 링크 DVI 신호를 입력 받아 신호의 왜곡 또는 감쇄 없이 Equalization & Driver 장비이다.

Features

○ 최대 1920 x 1200 / 60Hz 또는 1080i/P까지의 고해상도의 DVI-D 신호를 지원하며, 다수의 디스플레이 장치에(Project, PDP, LED TV, LCD Monitor 등.) 연결 사용한다.

○ Automatic input cable equalization 기능(최대 40Meter, 24AWG)

○ 전면 DVI-D 입력신호 유/무 검출 LED

○ 출력신호의 증폭기능(Preemphasis)

Panel Drawing



Specifications

○ DVI Part

- Input/Output number : 1
- Input/Output type : DVI-D Single link
- Input/Output connector : DVI-I Single/Dual link female
- Resolution rage : VGA ~ UXGA(640x480 ~ 1920x1200) or 1080p @ 60Hz
- Maximum bit rate : 2.25 Gbps
- Maximum pixel clock : 225 MHz

Max Digital Tech Co.,Ltd
Copyright 2006 Max Digital Tech.All rights reserved
Lead the 21st century with technology and service ..

Asia +65 81335582 Fax. +65 67828910
China +86 021 54249750 Fax. +86 021 54240199
Singapore +65 81335582 Fax. +65 67828910
Korea +82 2 2026 1200 Fax. +82 2 2026 1217

MDVI-30A

DVI REPEATER

장비개요 및 성능

○ Case & Power Part

- Power source : DC 5V, 2A(Power adaptor)
- Temperature : 0℃ ~ 40℃
- Power consumption : Below 10Watt
- Type : desk type
- Dimensions : 68(W) * 78(H) * 25(D) mm

Max Digital Tech Co.,Ltd

Copyright 2006 Max Digital Tech.All rights reserved

Lead the 21st century with technology and service ..

Asia	+65 81335582	Fax. +65 67828910
China	+86 021 54249750	Fax. +86 021 54240199
Singapore	+65 81335582	Fax. +65 67828910
Korea	+82 2 2026 1200	Fax. +82 2 2026 1217