

COMBO / TWIN

RHEOMETER + MOONEY VISCOMETER

콤보 / 트윈

본 시험 장비는 레오메타와 무늬점도계를 하나의 바디에 구성하여 공간 효율성 및 가격 경쟁력을 높인 제품입니다. 1대의 PC로 2대의 장비를 동시에 테스트하고 데이터를 관리하는 것이 가능합니다. 레오메타와 무늬점도계를 조합한 구성과 레오메타 혹은 무늬점도계만 조합으로 주문이 가능합니다. 국내뿐만 아니라 해외에도 널리 보급되어 있으며 우수한 기계적 특성과 사용자 친화적인 소프트웨어 인터페이스를 통한 사용 및 유지 보수가 간편한 장점이 있습니다.

The COMBO (TWIN) testing instrument is a combination of rheometer and mooney viscometer which enables not only size efficiency but also cost savings. A single PC fully controls these two instruments, individually and simultaneously, with ultimate convenience. Our latest software enables straightforward display of results, and data can be stored and easily managed on the instrument PC. Orders can also be made for twin rheometer and/or twin mooney viscometer.

SPECIFICATIONS

POWER	AC 220V 60Hz (50Hz : Option)
ELECTRICAL POWER	2.5KW
MOVEMENT	Geared Motor Operation
TEMP. RANGE	Ambient temp. +10 ~ 200°C (230°C : Option)
TEMP. CONTROL	Digital P.I.D Control
TEMP. PROBE	PT 100Ω
COMPRESSED AIR	4kg/㎠ (4.1bar, 60psi)
CONTROLLED BY	Windows OS COMBO Software
ACCESSORIES INCLUDED	Air regulator, O-ring, O-ring guide, Sample remover(Brass brush, Brass bar), Operation manual, Cable, Program CD, Extra fuse, Torque standard(MDR) Height gauge(MOONEY)
DIMENSIONS	752(W) × 610(D) × 1,110(H) mm
WEIGHT	Approx. 200kg
TYPE SELECT	Various combination of Rheometer and Mooney Viscometer avaliable. Ex) MDR(ODR) with Mooney, Rheo Twin or Mooney Twin



