Multi Room Drying Oven
다연실 건조기

- 초자기구건조, 멸균, 식품의 건조및 수분측정, 항온실험, 도장, 전자부품, 건축재료의 건조 등
- 2실, 3실, 4실의 온도가 각각 조절되어 다양한 온도 변화 실험가능.
- 온도분포도가 균일하고 정밀한 열풍순환방식
- Stainless 재질, 문에 진공열처리된 투시창이 부착되어 문을 열지 않고 내부관찰이 용이.
- 과열방지장치 장착
- Door interlock switch 부착 – Door open시 가열 정지로 히터 수명연장

DS-80C2



DS-80C3



Soil sterilizer 내부모습



DS-80C2-R



DS-80C2-R Two room
(in) 500 x 600 x 900(H)mm
(out) 1400 x 750 x1200(H)mm

DS-80C4



		DS - 80C2	DS - 80C3	DS - 80C4
Type		Forced convection type		
Main controller		Microprocessor digital displayed Auto-tuning multi-functional P.I.D controller (Temp, Time) / per room		
Temperature	Range	Ambient to 260℃		
	Accuracy	±0.3℃ at 140℃		
Timer		99min. 59sec. or 99hr. 59min. or 99days 23hours or continuous selectable		
Dimensions (WxDxH)mm	In	500 x 500 x 500 x 2room	500 x 500 x 500 x 3room	500 x 500 x 500 x 4room
	Out	1100 x 770 x 1360	1100 x 770 x 1860	1700 x 800 x 1660
Capacity		250 L	375 L	500 L
Material (In/Out)		Stainless steel (SUS 304) / Steel plate with powder coating(SCP-1)		
Circulation		60W blower fan x 2ea	60W blower fan x 3ea	60W blower fan x 4ea
Air vent exhaust hole		ID 40mm x 2 hole		
Insulation		Ceramic and glass wool board		
Shelves		SUS 3ea (per room)		
Door (Packing/Key)		Silicon rubber / Lock system		
Window		Three fold tempered glass(5mm)		
Safety system		Over heat protector, Power breaker		
Power(AC220V, 60Hz)		2.4Kw	3.6Kw	4.8Kw