100/1000Mbps TP 24포트 이더넷 10G 광스위치

100/1000Mbps TP 24포트 + 10G SFP 4슬롯



SFC4100T

- TP Auto-Negotiation, Auto MDI-X
- 웹 기반 매니지먼트, SNMP 매니지먼트 지원
- IGMP Snooping 지원
- IEEE 802.1p QoS, VoIP QoS, 1Q-in-Q 기능 지원
- 802.3ad Link Aggregation Control Protocol (LACP)
- 네트워크 보안을 위한 IEEE 802.1x 사용자 인증 지원
- 네트워크 에러 및 트래픽 분석을 위한 Port Mirroring 지원
- IEEE 802.1d & IEEE 802.1w Rapid Spanning Tree 지원

제품사양

표준	- Standard	IEEE 802.3 10Base-T IEEE 802.3ad Port trunk with LACP IEEE 802.1Q VLAN Tagging IEEE 802.3ae 10Gbps Ethernet IEEE 802.3u/x/z 100Base-TX/FX, Gigabit SX/LX IEEE 802.1w Rapid spanning tree protocol IEEE 802.1x Port Authentication Network Control
인터페이스	- RJ45 포트	10/100/1000Mbps TP 4포트, Auto-Negotiation, Auto MDI-X
	- 광포트	10G SFP 4슬롯, Speed auto detection
	- LED 표시	System: Power Ports: 10/100/1000Mbps Link/Act/Speed, SFP Link
성능	- Back Plane	Switching Fabric 128Gbps, 16K MAC Address table
	- Layer 2	Management Interfaces: Console, Telnet, Web Browser, SNMPv1, v2c, SNMP v3 VLAN: 802.1Q Tagged Based VLAN, Port VLAN, Q-in-Q, Private VLAN Edge (PVE) Spanning Tree: IEEE 802.1D, IEEE 802.1w Rapid Spanning Tree, IEEE 802.1s MSTP IEEE 802.3ad LACP / Static Trunk, IGMP (v1/v2/v3) Snooping IP-Based ACL / MAC-Based ACL, 802.1Q VLAN tag QoS
동작환경	- 온도범위	동작온도: 0˚C ~ 50˚C, 보관온도: -40℃ ~ 70℃
	- 습도	0 ~ 90% (이슬이 맺히지 않을 것)
입력전원		110~240VAC, 47/30Hz
크기		440mm (W) x 230mm (D) x 44mm (H), 1U

주문정보

모델명	사양
SFC4100T	100/1000Mbps TP 24포트 + 10G SFP 4슬롯
SFP+10G-LR	SFP(10.31Gps) 광모듈, 싱글모드, 전송거리 10km, 1310nm, LC 커넥터
SFP-SX	SFP(1.25Gbps) 광모듈, 멀티모드, 전송거리 220/550m, 850nm, LC 커넥터
SFP-LX	SFP(1.25Gbps) 광모듈, 싱글모드, 전송거리 20Km, 1310nm, LC 커넥터