MTS-15-2

Touch Panel

MDTC

Equipment Overview & Function

Max Digital Tech Co., Ltd http://www.maxdigital.co.kr

■ Description

○ 15″ Touch Panel is designed to work with Control PC, Main Control Unit (MMCU-100S, 150S, 200S, 150S, 300S etc.).

■ Features

○ LCD Touch Panel Monitor is connected to PC by USB port, used without keyboard/mouse and it takes five-ultrasonic cables.

■ Panel Drawing



■ Specifications

○ General Part

- Case/bezel color : Dark gray
- Display Size : 15″ diagonal
- Useful screen area : Horizontal: 12.0" (304 mm), Vertical: 9.0" (228 mm)
- Monitor dimensions : Width: 13.8" (350 mm), Height (inc. base): 12.2" (310 mm), Depth (inc. base): 6.9" (175 mm)
- Resolution : 1024 x 768
- Colors : 16.2 million with dithering
- Brightness LCD panel : 250 cd/m2
- Touchscreen : IntelliTouch (five-ultrasonic cables)
- Touch Interface : Dual (Serial/USB)
- Response time : 17 msec (typical)
- Viewing angle (typical, from center) : Horizontal (left/right): ±60° or 120° total, Vertical (up/down): 40°/60° or 100° total
- Contrast ratio : 400:1 (typical)
- Input video format : RGB analog
- Input sync format : Separate H & V sync, composite sync, sync-on-green
- Input video signal connector : Mini D-Sub 15-Pin VGA type
- Input frequency : Horizontal: 31.5-60.2 kHz, Vertical: 56.3-75 Hz
- Vesa mount : 75 mm
- Agency approvals : UL/CUL, FCC, CE, TÜV-GS, VCCI, IC, C-Tick

○ Power Part

- Power source : AC100-240V , 50/60Hz

MAX
Max Digital Tech Co.,Ltd
Copyright 2006 Max Digital Tech.All rights reserved
Lead the 21st century with technology and service ..

Asia	+65 81335582	Fax. +65 67828910
China	+86 021 54249750	Fax. +86 021 54240199
Singapore	+65 81335582	Fax. +65 67828910
Korea	+82 2 2026 1200	Fax. +82 2 2026 1217