Full HD 2M IP PTZ Camera with electro-polished 316L Stainless Steel housing

SWAN
Shipboard Wireless Area Network

SWAN-MPT-20HD



FEATURES

- Electro-polished 316L stainless steel
- IP67 rated - protected against heavy seas
- Full HD(2MP) IP Camera
- Built-in Wiper, Fan/Heater
- Integrated with Washer Pump
- 20x optical zoom / 12x digital zoom (Total 240x zoom)
- 0.5° to 60°/sec. (proportional to zoom)
- Pan 360° (Endless), Tilt 180°

SPECIFICATION

MODEL	SWAN-MPT-20HD
CAMERA & MECHANICAL	
Image Sensor	1/2.8" 2 Megapixel CMOS (Sony)
S/N Ratio	50 dB (Weight ON)
Focus / Zoom	F 1.6~3.5, f=4.7~94mm 20x opcial zoom,12x digital zoom
Min. Illumination	Color: 0.5Lux (1/30 sec, 50%, High Sensitivity mode ON) Color: 1.7Lux (1/30 sec, 50%, High Sensitivity mode OFF) BW: 0.095Lux (1/30 sec, 50%, High Sensitivity mode ON) BW: 0.3Lux (1/30 sec, 50%, High Sensitivity mode OFF)
Function	128 Presets, 8 Scans, 4 Tours, 8 Privacy Zone
Speed	0.5° to 60°/sec. (proportional to zoom), 60°/sec Preset Recall Speed
Angle	Pan 360° (Endless), Tilt 180°
VIDEO COMPRESSION	
Compression Type	H.264(MPEG4 AVC) @L3.0 / MJPEG / MPEG4
Resolution	1080p / 720p / D1 / 4CIF / VGA / CIF / QVGA / QCIF
Bitrate / FPS	32Kbps ~ 6Mbps / 30PFS @1920x1080p, 60FPS @1280x720p
Streaming	H.264 Dual Stream or Simultaneous H.264 and MJPEG
EXTERNAL I/O	
Reset Button	Restore to default setting (Network, Password and etc)
NETWORK	
Ethernet	Ethernet (10/100/1000 Based-T), RJ45 Connector
Protocol	TCP, IP, HTTP, DHCP, PPPoE, FTP, DNS, DDNS, NTP, ICMP, SNMP, SMTPE, UPnP, RTP, RTSP, Onvif
GENERAL	
Material	Stainless steel 316L
IP Rate	IP67
Approvals	CE
Power Requirement	AC220V, 1A
Operating Temp.	-20°C ~ 50°C
Weight	Approx. 20 kg (Net)
Dimension	341(W) x 246(D) x 393(H) mm

DIMENSION

Unit : mm

