




KS-RPM *Triple*
RPM METER

KS-RPM Portable
KS-RPM PCB

Merits and Feature

- ✓ Engine RPM is immediately identificable through LCD.
- ✓ Supported by the wireless communication, the communication line is not required.
- ✓ You do not need any extra power supply(Built-in rechargeable battery).
- ✓ Measuring temperature of engine oil is available.

Composition

- The Machine Body, Charger Adapter
- Sound Sensor Cable
- Vibration Sensor Cable
- Battery Sensor Cable
- Cigar Jack Cable

Option

- Bluetooth
- Oil Temperature(Themistor)

Specification

- **Display**
  - 4 Digit 7 Segment LCD
  - BackLight
- **Analysis Range**
  - RPM : 10 rpm ~ 5000 rpm
  - Oil Temp. : 0 ~ 200.0 ℃
- **Resolving Power**
  - RPM : 10 rpm
  - Oil Temp. : 0.1 ℃
- **Power Supply**
  Built-in rechargeable battery(Be rechargeable by charger adapter)
- **Operating Temperature**
  - -10 ~ 40℃
- **Interface**
  - RS232, Wireless(Bluetooth)
- **Dimensions**
  - Portable : 90 ㎜(W) x 32.5 ㎜(D) x 152 ㎜(H)
  - PCB : 95 ㎜(W) x 90 ㎜(H)
- **Cable Length**
  - 2 m (Sound, Vibration, Temperature Cable)
  - 3 m (Battery Cable)
  - 1 m (Cigar Jack Cable)

KS RnD CO., LTD.
www.ksrnd.com