MTS-17-2

Touch Panel

MDTC

Equipment Overview & Function

Description

○ 17" Touch Panel is designed to work with Control PC, Main Control Unit (MMCU-100S, 150S, 200S, 150S, 300S etc.).

Features

○ LCD Touch Panel Monitor is connected to PC by USB port, used without keyboard/mouse and it takes five-ultrasonic cables.

Panel Drawing



Specifications

○ General Part

- Case/bezel color : Dark gray
- Display Size : 17"형 diagonal
- Useful screen area : Horizontal: 13.4" (338 mm), Vertical: 10.6" (270 mm)
- Monitor dimensions : Width: 15.4" (391 mm), Height (inc. base): 14.4" (366 mm), Depth (inc. base): 8.0" (203 mm)
- Resolution : 1280 x 1024
- Colors : 16.2 million with dithering
- Brightness LCD panel : 280 cd/m2
- Touchscreen : IntelliTouch (five-ultrasonic cables),Touch Interface : Dual (Serial/USB)
- Response time : 25 msec (typical)
- Viewing angle(typical, from center) : Horizontal (left/right): ±70° or 140° total, Vertical (up/down): 63°/60° or 123° total
- Contrast ratio : 450:1 (typical)
- Input video format : RGB analog
- Input sync format : Separate H & V sync, composite sync, sync-on-green
- Input video signal connector : Mini D-Sub 15-Pin VGA type
- Input frequency : Horizontal: 31.5-80 kHz, Vertical: 56.3-75 Hz
- Vesa mount : 100 mm
- Agency approvals : UL/cUL, FCC, CE, TÜV-GS, VCCI, IC, C-Tick

○ Power Part

- Power source : AC100-240V , 50/60Hz

MAX
Max Digital Tech Co.,Ltd
Copyright 2006 Max Digital Tech.All rights reserved
Lead the 21st century with technology and service ..

Asia +65 81335582 Fax. +65 67828910
China +86 021 54249750 Fax. +86 021 54240199
Singapore +65 81335582 Fax. +65 67828910
Korea +82 2 2026 1200 Fax. +82 2 2026 1217