



FEATURES

- 165MHz Digital Video Bandwidth
- DVI-I input/output
- 5 channel output
- DDC read through Channel no.1 only
- 90V ~ 260V 50/60Hz Auto switching AC input
- Compact Size

K-6162 receives input of Digital Serial Data (R, G, B), Sync signal and control signal and then distributes them without amplification, attenuation and distortion. It can be used to inspect reliability of TFT-LCD Monitor and PDP, and it can be equipped on burn-in racks and showroom with using Panel Link method.

SPECIFICATIONS

Digital Video / Sync Output	Video Bandwidth : 165MHz
Channel	Output connector : DVI-I, Output Channel : 5 channels
	Input signal : TX2+, TX2-, TX1+, TX1-, TX0+, TX0-, TXC+, TXC-,Input connector :DVI-I
EDID	DDC pass through output channel 1
Miscellaneous	Frequency : 50~60Hz, Voltage : 90V~260V auto switching Power consumption : 10VA(Max)
	Operation Humidity/Temperature : 80%/-10℃~60℃ Dimensions (H x W x D) : 41 x 354 x 146 mm
Accessory	Power Cable : K-2014

* All specifications are subject to change without any notice.

K-6300 ANALOG VIDEO SIGNAL DISTRIBUTION BUFFER





FEATURES

- 300MHz Analog Video Bandwidth
- R, G, B, HS, VS, BNC Input
- 5 Channels 15-pin D-sub Output
- Compact Size

K-6300 receives Analog Video (Red, Green, Blue) and Sync signals(HS, VS) and then distributes them without amplification, attenuation and distortion. It is suitable for reliability test of high resolution CRT Monitor, TFT LCD Monitor and PDP. It can be applied to various area, e.g. Showroom, conference room and school.

SPECIFICATIONS

Analog Video / Sync Output	Video Bandwidth : 300MHz, Attenuation : 300Mhz -3.0dB
	Video Output level : 0.7Vp-p, (75ohms terminal), Separate sync Output level : 3.0 ~ 4.5Vp-p
	Output level control : internal VR, Output connectors : 15-Pin D-sub (5 channels)
Signal Input	Input Signal : R, G, B, HS, VS, Input connectors : R, G, B, HS, VS, BNC Connectors
Miscellaneous	Frequency : 50~60Hz, Voltage : 90V~260V auto switching Power consumption : 20VA(Max)
	Operation Humidity/Temperature : 80%/-10℃~60℃ Dimensions (H x W x D) : 44 x 307 x 144 mm
Accessory	Power Cable : K-2014

* All specifications are subject to change without any notice.