MRD-124

RGB Distributor Amp

Equipment Overview & Function

Description

○ This is a one input, 24 output R.G.B.H.V distribution amplifiers.

Features

○ It distributes each out to different R.G.B.H.V display devices such as projector, RGB SW etc.

○ Its outstanding feature provides low frequency loss with minimum noise.

○ ON / OFF Switch is available in front of the device. D-sub Connector at input/output terminal makes operation easy.

Panel Drawing



Specifications

○ Video Part

- Input/Output number : 1 x 24
- Input/Output type : RGBHV
- Input/Output connector : d-sub 15pin
- Input/Output level : analog RGB : 1.2Vp-p Max, H-Sync, V-Sync : TTL level
- Input/Output impedance : 75Ohm ± 1%
- Bandwidth : 600 MHz (-3 dB), fully loaded

Max Digital Tech Co.,Ltd

Copyright 2006 Max Digital Tech.All rights reserved

Lead the 21st century with technology and service ..

Asia	+65 81335582	Fax. +65 67828910
China	+86 021 54249750	Fax. +86 021 54240199
Singapore	+65 81335582	Fax. +65 67828910
Korea	+82 2 2026 1200	Fax. +82 2 2026 1217

MRD-124

RGB Distributor Amp

Specifications

○ Case & Power Part

- Power source : AC 85 ~ 240V, 50 ~ 60Hz
- Temperature : 0℃ ~ 40℃
- Power consumption : below 30Watt
- Type : 19″ Rack type
- Dimensions : 483(W) * 89(H) * 300(D) mm

Max Digital Tech Co.,Ltd

Copyright 2006 Max Digital Tech.All rights reserved

Lead the 21st century with technology and service ..

Asia	+65 81335582	Fax. +65 67828910
China	+86 021 54249750	Fax. +86 021 54240199
Singapore	+65 81335582	Fax. +65 67828910
Korea	+82 2 2026 1200	Fax. +82 2 2026 1217