MMS-800HD

HD SDI Matrix Switcher

장비개요 및 성능

Max Digital Tech Co., Ltd http://www.maxdigital.co.kr

Description

○ 본 장비는 8개의 입력된 Digital Video HD-SDI(또는 SDI)을 선택하여 8개의 해당출력으로 절체시켜주는 고해상도 Digital Video 분배, 교환장치이다. (3G, HD-SDI, SDI)

Features

○ SMPTE 259M, SMPTE 292M,SMPTE 344M, and SMPTE 424M Compliant

○ 전면의 조작 KEY로 원하는 입 • 출력을 제어할 수 있으며, RS-232C 및 Lan Port를 이용하여 Remote 제어가 가능토록 되어 있다.

○ 전원 OFF시에도 최종 연결 상태 값을 가지고 있도록 Memory Back-up 기능이 있다.

○ PGM, CALL 기능이 있어 신호의 연결 값을 저장, 실행 할 수 있다.

○ 전면에 입력의 연결상태를 확인 할 수 있는 Display Panel이 부착 되어 있다.

○ 외부 입력신호와 동기를 맞추기 위한 Sync 단자가 있다.

Panel Drawing



Specifications

○ General Part

- Gain : Unity
- Maximum data rate : 2.97Gbps
- Input/Output connector : BNC
- Auto data rate lock : Yes
- Operation standards : SMPTE 292M, SMPTE 344M, SMPTE 259M, SMPTE 424M compliant

○ Input cable equalization distance

- Belden 1694A cable : HD-SDI(150m), SDI(300m)
- Belden 1505A cable : HD-SDI(100m), SDI(200m)

Max Digital Tech Co.,Ltd

Copyright 2006 Max Digital Tech.All rights reserved

Lead the 21st century with technology and service ..

Asia	+65 81335582	Fax. +65 67828910
China	+86 021 54249750	Fax. +86 021 54240199
Singapore	+65 81335582	Fax. +65 67828910
Korea	+82 2 2026 1200	Fax. +82 2 2026 1217

MMS-800HD

HD SDI Matrix Switcher

장비개요 및 성능

Max Digital Tech Co., Ltd http://www.maxdigital.co.kr

○ Video Part

- Input/Output number : 8 x 8
- Input/Output type : SDI or HD-SDI, 3G digital component video, 75ohm
- Input/Output connector : BNC
- Input/Output level : 0.8 Vp-p ±10%
- Return loss : > 15dB
- Equalization : Automatic
- Re-clocking : Automatic
- Jitter : <0.2 UI

○ Remote Control Part

- Serial control : 1 RS-232 and 1 Lan Port

○ Case & Power Part

- Power source : AC 85 ~ 240V 50 ~ 60Hz
- Temperature : 0℃ ~ 40℃
- Power consumption : below 20Watt
- Type : 19″ Rack type
- Dimensions : 483(W) * 44.5(H) * 300(D) mm



Max Digital Tech Co.,Ltd
Copyright 2006 Max Digital Tech.All rights reserved
Lead the 21st century with technology and service ..

Asia	+65 81335582	Fax. +65 67828910
China	+86 021 54249750	Fax. +86 021 54240199
Singapore	+65 81335582	Fax. +65 67828910
Korea	+82 2 2026 1200	Fax. +82 2 2026 1217