CAB-H2000ATIR



FEATURES

- Max. 2M(1920 x 1080) @30fps
- Min. illumination 0.1Lux (Color), 0.00Lux (IR LED ON)
- Built-in 3.5~16mm Auto-Focus lens
- Day&Night (Auto ICR)
- WDR / 3DNR
- 42 IR LEDs
- OSD
- DC12V

SPECIFICATION

MODEL	CAB-H2000ATIR
CAMERA	
Image Sensor	1/2.8" 2.1M Progressive Scan CMOS sensor (SONY)
Total Pixels	2000(H) x 1241(V)
Scanning System	Progressive Scan
Shutter Speed	1/25~1/120sec
S/N Ratio	More than 50dB
Lens	3.5~16mm Auto-Focus Lens
Min. Illumination	0.1 Lux (F1.2) / 0.00Lux (IR LED On)
Day & Night	Auto / Day / Night (ICR)
AGC	Normal, High
White Balance	AUTO / PRESET / MANUAL
WDR / BLC	OFF / WDR / BLC
DNR	OFF / MID / HIGH
DSS	OFF, x2, x3, x4
Image setting	Brightness, Sharpness
Other Functions	Image Flip, Mirror/ACE, Privacy masking
IR LED and Sensor	IR LED 42EA (850nm, 30°), Sensor 1EA
IR Visible Range	Max. 40m
GENERAL	
Sensor In/Out	Built-in 1 Output
Video Out	HD-SDI, SMPTE-292M (1280X720p/59.94Hz, 1280X720p/50Hz 1920X1080p/59.94Hz, 1920X1080p/50Hz)
Power	DC 12V, 12W
Communication	RS-485 Protocol : Pelco-D , Pelco-P
Approvals	FCC, CE, IP66, ROHS
Operating Temp.	-40°C ~ 50°C
Weight	2.5 Kg
Dimension	100(W) x 97(H) x 300(D) mm

DIMENSION

Unit : mm

