TSK-950 (Long Range CCD)



- PERFORMANCE

CPU :	32Bit
Scan rate :	300 Scans per Second
Resolution :	4 mil (0.1mm)
Photo Sensor :	3648 Pixel Linear CCD
Illumination :	660nm Visible Red LEDS
Field Width :	120mm (15mil)
Depth of field :	0mm~450mm
Symbologies :	UPC/EAN/JAN, Code39, Interleaved 2 of 5 Standard 2 of 5, Matrix 2 of 5, Industrial 2 of 5, Codabar, Code128, MSI, Plessey, Code93, Code 3 of 5 GS1 DATABAR (Korean Postage)
Interface :	Standard RS-232C, Keyboard Wedge, USB, SERIAL USB

- MECHANICAL

Dimensions :	75mm X 51mm X 170mm
Weight :	120g
Body Material :	ABS Plastic

- ELECTRICAL

Power Supply :	5VDC ± 10%
Power Consumption :	28mA ~ 120mA

- DURABILITY

Trigger Switch :	1 million Actuations
Cable :	100,000 Bending at 90 degree with 500g weight, 1.8m
Shock Resistance :	1 meter drop onto Concrete Surface

- ENVIRONMENTAL

Temperature :	Operating : 0 ~ 50°C, Storage : -10 ~ 60°C
Humidity :	Operating : 10% ~ 80%, Storage : 10% ~ 95%
Mechanical Shock :	Functional after 1.5m (5ft) drops
ESD Protection :	Functional after 15kV discharge

Woolim e-Biz centerII 4F 184-1 Guro-3Dong Guro-Gu Seoul Korea Tel : 82-2-890-5440
Fax : 82-2-890-5443 URL:http://www.techscan.co.kr **TechScan Korea Co.,Ltd.**