TRUEN



TN-B236N15

- Sony 1/2” Progressive Scan CMOS
- H.265 / H.264 / MJPEG
- Max 60FPS @ 1920 x 1080
- X36 Optical Zoom
- X16 Digital Zoom
- SRT (Secure Reliable Transport)
- RTSP/RTMP/MPEG-TS
- ONVIF (Profile S, Profile G)
- True WDR
- Hybrid CBR
- Dual Power (DC/PoE)



www.truen.co.kr
os@truen.co.kr

TN-B236N15 Specifications

Basic Specifications	
Image Sensor	1/2” Sony CMOS Sensor
Lens type	AF, Auto Iris
Lens mount	Board type
Minimum illumination	Color : 0.048 Lux at 1/30sec, F1.6, 50IRE BW : 0.001 Lux at 1/30sec, F1.6, 50IRE
Lens (wide to tele)	36x optical zoom ; f= 6mm to 216mm
Shutter Speed	1/1 to 1/100000
Maximum Aperture Ratio	F1.5 ~ F4.8
Angle of View	Horizontal : 58.5°(wide) ~ 2.1°(tele)
Privacy masking	8 regions
Flip mode	Horizontal, Vertical
Image enhancement	AE, AWB,TDN, DNR, BLC, WDR, DSS, DIS, Defog, Color Enhancement
IR LED	N/A
Video	
Compression	H.265/H.264/MJPEG
Frame rate	Max 60fps @ 1920x1080
Bitrate	Primary : 32Kbps ~ 16Mbps, Secondary : 32Kbps ~ 4Mbps
Resolution	320x240 ~ 1920x1080
Streaming	Quad Streaming - Primary : H.265/H.264, Secondary x 3 : H.265/H.264/MJPEG
Bitrate Control	CBR / VBR / Hybrid / Adaptive CBR / Smart CBR
Burn-in OSD	Multi-lingual
Output	Composite
Audio	
Compression	G.711 / AAC(Option)
Sampling rate	G.711 : 8 KHz, AAC(Option): 32 kHz / 44.1 kHz / 48 kHz
Bitrate	G.711 : 64Kbps, AAC(Option): 64Kbps/128Kbps
Streaming	G.711 : Full-duplex, AAC(Option): Full-duplex
Input/Output	1 x Line-In (mono), 1 x Line-Out (mono)
Network	
Protocol	IPv4/v6, TCP, UDP, IGMP(Multicast), ICMP, DHCP, HTTP, HTTP, FTP, SNMP, SMTP, UPnP, WS-Discovery, Zero Configuration, NTP, SRT, MPEG-TS, RTP, RTSP, RTMP, DDNS
Security	Password protection, IP address filtering, HTTPS encryption
API	Truen protocol/SDK, ONVIF, PSIA, MPEG-TS
Interface	Ethernet 10/100 base-T (RJ-45)
Event / Alarm	
Event sources	Motion, Sensor input, Client disconnection
Event actions	Notification(E-mail), FTP, PTZ preset, Alarm control, Recording
External devices	1 x Sensor-In (dry contact, NO/NC) 1 x Alarm-Out (dry contact, NO) 1 x RS-485 port : PTZ control etc.
General	
Power Supply	Min DC12V/1.5A, PoE(Power over Ethernet) : 802.3af
Power Consumption	DC12V/PoE : Max DC12V/4.5W
Operating Temperature	-10°C ~ 50°C (14°F ~ 122°F)
Storage Temperature	-10°C ~ 50°C (14°F ~ 122°F)
Operating Humidity	20% ~ 80% RH
Storage Humidity	20% ~ 80% RH
Edge Storage	SD/SDHC/SDXC slot (Max 512GB)
Dimensions (W x H x D)	79.0mm X 227.0mm X 79.0mm
Weight	1,100g

DIMENSION

(mm)









© Truen Co., Ltd. All rights reserved. Reproduction in whole or in part without written permission is prohibited. Features and specifications are subject to change without notice. The values for mass and dimensions are approximate. Please contact for specific models available in your region.