CAN-H2000AT



FEATURES

- Max. 2M(1920 x 1080) @30fps
- Min. illumination 0.1Lux @ F1.2, 30IRE (Color)
  0.01Lux @ F1.2, 30IRE (B/W)
- Built-in 3.5~16mm Auto-Focus lens
- Day&Night (Auto ICR)
- WDR / 3DNR
- OSD
- DC12V

SPECIFICATION

MODEL	CAN-H2000AT
CAMERA	
Image Sensor	1/2.8" 2M Progressive Scan CMOS sensor (SONY)
Total Pixels	2000(H) x 1241(V)
Scanning System	Progressive Scan
Shutter Speed	1/25~1/120sec
S/N Ratio	More than 50dB
Lens	3.5~16mm Auto-Focus Lens
Min. Illumination	COLOR : 0.1Lux @ F1.2, 30IRE B/W : 0.01Lux @ F1.2, 30IRE
Day & Night	Auto / Day / Night (ICR)
AGC	Normal, High
White Balance	AUTO / PRESET / MANUAL
WDR / BLC	OFF / WDR / BLC
DNR	OFF / MID / HIGH
DSS	OFF, x2, x3, x4
Image setting	Brightness, Sharpness
Other Functions	Image Flip, Mirror/ACE, Privacy masking
GENERAL	
Sensor In/Out	Built-in 1 Output
Video Out	HD-SDI, SMPTE-292M (1280X720p/59.94Hz, 1280X720p/50Hz 1920X1080p/59.94Hz, 1920X1080p/50Hz)
Power	DC 12V, 5W
Approvals	FCC, CE, IP68, ROHS
Operating Temp.	-40°C ~ 50°C
Weight	1.3 Kg
Dimension	Ø139 x 121.8(H) mm

DIMENSION

Unit : mm

