MULTI SIGNAL DISTRIBUTOR

MULTI SIGNAL DISTRIBUTOR

K-6258H

>>





- Multi signal distribution
- 250MHz Video band width (-3.0dB)
- Output level control
- HDMI V1.3 Distribution

K-6258H는 HDMI V1.3 Spec을 지원하며 PC 신호(Red, Green, Blue, HS, VS), 복합 영상 신호(CVBS), S-Video(Y/C), 컴포넌트 신호(Y, Pb, Pr) 및 Audio(R, L), DVI 신호를 감쇄 및 왜곡 없이 분배 함으로 TFT-LCD TV, PDP, D-TV등 Multi 신호를 입력 받는 Display기기에 적합한 종합 신호 분배 장비입니다.

K-6258H is distributing PC signal(RGB, HS, VS), Digital signal(DVI), HDMI, CVBS, S-Video (Y/C) Component (YPbPr) and Audio R, L without any amplification, attenuation and distortion.
It is signal distribution equipment which is suitable to TFT-LCD, TV, PDP, D-TV etc.

SPECIFICATIONS

PC (RGB, HS, VS)	Video band width : 250MHz (-3.0dB 75 ohm terminal)
	Video output level : 0.7Vp-p (75 ohm terminal)
	Sync output level : 3.0 ~ 3.5 Vp-p
	Input connector : 15P D-Sub
	Output connector : 5 CH (15P D-Sub)
Digital (DVI)	Video band width : 165MHz
	Input connector : DVI-I
	Output connector : 5 CH (DVI-I)
	DDC read through CH no. 1 only
HDMI	Video band width: 165MHz (HDMI V1.3)
	Input connector : HDMI
	Output connector : 5 CH (HDMI)
	EDID data read through CH no. 1 only
Component (YPbPr)	Video band width : 250MHz (-3.0dB 75 ohm terminal)
	Video output level : 1.0Vp-p (75 ohm terminal)
	Input connector : RCA
	Output connector : 5 CH (RCA)
CVBS Audio R, L	Video band width : 250MHz (-3.0dB 75 ohm terminal)
	Audio band width : 20 ~ 20,000Hz
	Video output level : 1.0Vp-p (75 ohm terminal)
	Input connector : RCA
	Output connector : 5 CH (RCA)
S-Video (Y/C)	Video band width : 250MHz (-3.0dB 75 ohm terminal)
	Video output level : 1.0Vp-p (75 ohm terminal)
	Input connector : S-Video Jack
	Output connector : 5 CH (S-Video Jack)
Miscellaneous	AC 90 ~ 260V (50/60Hz Free)
	Auto switching power consumption: 25VA (max)
	Operation Temp./Humidity: 0°C ~ 40°C / below than 80%
	Dimensions (H x W x D): 300 x 415 x 192(mm)

* All specifications are subject to change without any notice.