MULTI SIGNAL DISTRIBUTION BUFFER
K-6256A

FEATURES

- 6CH output (CVBS, Y/C, Component, PC)
- Multi Signal Distribution
- 250MHz Video Bandwidth (-3.0dB)
- Possible to control output level

K-6256A distributes PC Signal (Red, Green, Blue, HS, VS), Digital Signal (TMDS), HDMI, CVBS, S-Video (Y/C), Component Signal(Y,Pb,Pr) and Audio(R,L) Signal without amplification, attenuation and distortion.
It is a signal distribution equipment which is suitable for TFT-LCD, TV, PDP, D-TV and etc..





MULTI SIGNAL DISTRIBUTION BUFFER
K-6256

FEATURES

- Multi Signal Distribution
- 250MHz Video Bandwidth (-3.0dB)
- Possible to control output level

K-6256 distributes PC Signal (Red, Green, Blue, HS, VS), Digital Signal (TMDS), HDMI, CVBS, S-Video (Y/C), Component Signal(Y,Pb,Pr) and Audio(R,L) Signal without amplification, attenuation and distortion.
It is a signal distribution equipment which is suitable for TFT-LCD TV, PDP, D-TV and etc..





MULTI SIGNAL DISTRIBUTION BUFFER
K-6255

FEATURES

- Multi Signal Distribution
- 250MHz Video Bandwidth (-3.0dB)
- Possible to control output level

K-6255 distributes PC Signal (Red, Green, Blue, HS, VS), CVBS, S-Video (Y/C), Component Signal(Y,Pb,Pr), DVI and SCART Signal without amplification, attenuation and distortion.
It is a signal distribution equipment which is suitable for TFT-LCD TV, PDP, D-TV and etc..





MULTI SIGNAL DISTRIBUTION BUFFER
K-6254

FEATURES

- Multi Signal Distribution
- 250MHz Video Bandwidth (-3.0dB)
- Possible to control output level

K-6254 distributes PC Signal (Red, Green, Blue, HS, VS), CVBS, S-Video (Y/C) and Component (Y,Pb,Pr) Signal without amplification, attenuation and distortion.
It is a signal distribution equipment which is suitable for TFT-LCD TV, PDP, D-TV and etc..



