TV(Y/C) VIDEO SIGNAL DISTRIBUTION BUFFER

K-6034

FEATURES

- 250MHz Video Bandwidth (-3.0dB)
- 20KHz Audio Bandwidth
- -1.0 dB Attenuation at 75MHz

K-6034 distributes S-Video (Y/C) and audio signal without amplification, attenuation and distortion. It is a signal distribution equipment which is suitable for PDP and TV.



SPECIFICATIONS

Signal Output	Video Bandwidth : 250MHz, -3.0dB Audio bandwidth : 20KHz
	Video Output level : 1.0Vp-p, (75ohms terminal), Output level control : rear panel VR
	Output Port : 4P Mini Din(Y/C), Output Channel : 5 channels, 10 channels
Signal Input	Video Input Signal : Y/C Connector input, Audio Input connectors : R, L RCA input
Miscellaneous	Frequency : 50~60Hz Voltage : 90V~260V auto switching Power consumption : 20VA(Max)
	Operation Humidity/Temperature : 80%/-10℃~60℃, Dimensions(H x W x D) : 92 X 202 X186(mm)
Accessory	Power Cable : K-2014

* All specifications are subject to change without any notice.

TV(CVBS) VIDEO SIGNAL DISTRIBUTION BUFFER

K-6033

FEATURES

- 250MHz Video Bandwidth (-3.0dB)
- 20KHz Audio Bandwidth
- -1.0 dB Attenuation at 75MHz

K-6033 distributes CVBS and audio signal without amplification, attenuation and distortion. It is a signal distribution equipment which is suitable for PDP and TV.



SPECIFICATIONS

Signal Output	Video Bandwidth : 250MHz, -3.0dB Audio bandwidth : 20KHz
	Video Output level : 1.0Vp-p, (75ohms terminal), Output level control : rear panel VR
	Output Port : RCA, Output Channel : 5 channels, 10 channels
Signal Input	Video Input Signal : CVBS(RCA) input, Audio Input connectors : R, L (RCA) input
Miscellaneous	Frequency : 50~60Hz Voltage : 90V~260V auto switching Power consumption : 20VA(Max)
	Operation Humidity/Temperature : 80%/-10℃~60℃, Dimensions(H x W x D) : 92 X 202 X186(mm)
Accessory	Power Cable : K-2014

* All specifications are subject to change without any notice.