RHINO RHQ Quick coupler



RHQ 705 | RHQ 713 | RHQ 718 | RHQ 722 | RHQ 730



RHQ 704 | RHQ 705 | RHQ 713 | RHQ 722 | RHQ 730



RHQ 702 | RHQ 703 | RHQ 713 | RHQ 722 | RHQ 733



Benefits

- Wide application with wide pin-to-pin distance
- Outstanding durability by using abrasion resistant high strength material
- Safety valve integrated cylinder and manual safety pin
- Low off-set height and up-to-date design



Specifications

ITEMS	Unit	RHQ 702			RHQ 703			RHQ 704		RHQ 705				RHQ 708			RHQ 713			RHQ 718	RHQ 720	RHQ 722			RHQ 730			RHQ 733
		K1	V1.Y1	D1.B1	K1	V1.V2	D1.B1	V1.V2	D1	H2	C1	V2	D2	C1	D2	V1	H1	V1	D4	H1	V1	H1	V1	D2	H1	H1	D1	D1
Overall length	mm	436	342	352	452	446	457	489	500	571				627	620	645	764	774	764	882	886	920	918	931	1,078			1,126
Overall height	mm	232	220	222	272	243	252	254	262	309	321	304	321	333	318	357	383	385	388	477	482	495	490	479	532	541		572
Overall width	mm	235	208		249	227	243	228	239	286	277	280	277	325	322	307	402	418	422	484	479	503	498	503	635			644
Working weight *1)	kg	32	26		40	36	39	45	47	69				82			160	160	163	255	255	280	278	280	460			528
Mounting width	mm	132	104.5		144	122	134	123	134	164	155	158	155	184	200	169	258	274	259	306	304	330	325	330	398	410	394	410
Mountable pin-to-pin	mm	174 - 217		104 - 147	174 - 217	160 - 204	191 - 236	182 - 228	191 - 236	255 - 303				291 - 349	287 - 353	284 - 338	380 - 439			405 - 507	405 - 507	445 - 516			488 - 603			539 - 606
Pin diameter	mm	30			35			40		45				45		60	65			70	70	80			90			100
Offset height	mm	150			160			160	165	170				200	180	200	230			280	280	290	285	270	315			310
																								S170W-V				
Applicable carrier																	R1300LC							S200W-V				
		P20 - MRX	EC15	SO15	P20 - MRX	EC25	S 30	EC35	SO 35	R55W-7	305.5	EC55B	S55-V				R1300W			R160LC-7	EW180B	RC220LC-7	EC210	S220LC-V	R290LC-7	EX290BLC	S290LC-V	S330LC-V
			Vio 15	Bobcat 322		EC 30	Bobcat 328	ECR 38				EW55B	S55-VG	307	S 75-V	ECR 88	R1300W-3	MX135WG	DX140W	R170DW-7	EW200B	RC200DW-7	EC225LS	S225LC-V	R290DLC-7			S340LC-V
						ECR 28	Bobcat 331					ECR58	S55W-V				R1300WM			R160LC-7		R210LC-7		S250LC-V	R250LC-7	MX295LC	S300LC-V	S360LC-V
													S55W-VG				R1400-7							S255LC-V				

Notes 1) Weight including the bracket pins and hoses
* Materials and specifications are subject to change without prior notice



