Multi Room Incubator
다연실배양기

- 미생물배양, 동식물 세포배양, 식품의 저장성 실험, 발아시험, 항온실험등 실험실의 기초장비
- 각 챔버별로 온도 및 시간을 각각 설정
- 선반높낮이 조절가능, 내부관찰을 위한 Inner safety glass door,내부온도 유출방지, 기기 소음의 극소화 과열방지, 과전류차단,
- 각종 안전장치 부착

DS-10S2



DS-10L2



DS-10L4



DS-10T



(in) 400 x 400 x 300mm

		DS - 10S2	DS - 10L2	DS - 10L4
Main controller		Microprocessor digital displayed Auto-tuning multi-functional P.I.D controller (Temp, Time)		
Temperature	Range	Ambient +5℃ to 70℃		
	Accuracy	±0.2℃ at 37℃		
Timer		99min. 59sec. or 99hr. 59min. or 99days 23hours or continuous selectable		
Dimensions (WxDxH)mm	In	500 x 500 x 700 x 2 rooms	500 x 500 x 980 x 2 rooms	500 x 500 x 980 x 4 rooms
	Out	620 x 660 x 1790	1280 x 660 x 1170	2560 x 660 x 1170
	Capacity	350 L	490 L	980 L
Material	In	Stainless steel (SUS 304)		
	Out	Steel plate with powder coating(SCP-1)		
Circulation fan		Sirico fan (per room)		
Safety system		Hydraulic over heating safety S/W		
Shelves		Adjustable 2ea (per room)	Adjustable 3ea (per room)	Adjustable 3ea (per room)
Power (AC220V, 60Hz)		0.7Kw	0.7Kw	1,4Kw