K-6100C COMPACT VIDEO PATTERN GENERATOR



FEATURES

- HDCP
- Analog RGB, Digital (DVI) support
- Maximum 50 mode of time data
- Maximum 50 of pattern data
- Possible to send and receive Timing, Pattern, EDID and control code
- Used with K-5400, Possible to set up function group
- ROM Program Upgrade by PC

SPECIFICATIONS

Analog Output	DOT Frequency : 162MHz
	H Frequency 200 Khz, V Frequency 200Hz
	Output port : R, G, B, HS, VS
	DDC : SDA, SCL
	Output Connector : 15Pin D-SUB
Digital Output	UXGA (1600 x 1200)
	DOT Frequency : 162MHz (max)
	Transmission Method : TMDS 24Bit One Pixel/One Clock
	Output : Tx2+/-(Red), Tx1+/-(Green), Tx0+/-(Blue), Txc+/-(Clock)
	Output connector : DVI-I
Miscellaneous	AC 85 ~ 264V (50/60Hz Free)
	Auto switching Power consumption : 1200mA
	Operating Temperature : -10℃ ~ 40℃
	Humidity : below than 80%
	Dimension(H x W x D) : 47 x 227 x 98
	Convenient connector exchange
Accessory	Power Cable:K-2014

* All specifications are subject to change without any notice.

K-5400 / K-5401 / K-5402

Remote Controller



K-5400

IR Port



K-5401

Remote Controller



K-5402

FEATURES

- Auto timing Parameter check
- Function Call & Edit
- Call Timing & Pattern
- Use for signal generator independently
- Easy program upgrade

* All specifications are subject to change without any notice.